

SHOWER SYSTEMS



OWNER'S MANUAL
CLEANING & CARE



SHOWER BASE CLEANING INSTRUCTIONS

The cross-linked cast acrylic surface of all MTI acrylic products is among the glossiest, highest quality surfaces available. Its hard, non-porous surface prevents dirt from accumulating and resists stains better than other materials. With normal use, cast acrylic will retain its beauty with only a minimal amount of care. To maintain the high gloss, elegant look of the cast acrylic surface, follow these simple steps:

Use common household, **non-abrasive** cleaners for most cleaning jobs (for example: a mild dish-washing detergent such as Ivory Liquid). Follow manufacturer's directions and precautions. **Do not use unless the product label specifically states that it is safe for acrylic.** Rinse well and dry with a soft, clean cloth. Be sure to check the product label. Some products, although not containing abrasives, WILL damage the acrylic over time. Never use any type of "scrubbing bubbles" or aerosol spray cleaners on your acrylic product unless it specifically states that it is safe for use on acrylic!

Never use abrasive cleansers. If any product feels gritty when rubbed between your fingers, do not use on the acrylic surface or controls as permanent damage will occur.

Do not allow your cast acrylic surface to come into contact with nail polish, nail polish remover, Wintergreen oil, dry cleaning solution, lacquer thinners, gasoline, pine oil, etc.

Remove dust and dry dirt with a soft, damp cloth.

Clean grease, oil, paint or ink stains with isopropyl (rubbing) alcohol. Dry with a clean, soft cloth.

Avoid using razor blades or other sharp objects that might scratch the surface. Small scratches can be removed by applying a thin coat of automotive polishing liquid and buffing lightly with a clean cloth. For deeper scratches, sand the surface lightly with a 400 grit "wet or dry" paper and buff with a fine grit buffing compound.

MTI strongly recommends a professional acrylic repair person for deep scratches or chips.

TEAK SHOWER TRAY INSTALLATION AND CARE

Teak shower trays by MTI are designed to fit each individual shower base. Simply set the tray in place! Your teak shower tray is built from one of the finest woods on our planet and will provide many years of service with little maintenance. You may choose to leave the finish natural or periodically wipe on teak oil or olive oil to the wood's surface. Both oils are inexpensive and can be found at you local hardware or grocery store respectively. You can also stain your new teak shower tray a darker wood tone if you desire. Any water-based stain may be used. Like the oils, it can be easily applied using a rag or sponge.

Your teak tray will need to be cleaned every 30-90 days, depending on usage. MTI recommends the mildest cleaner possible for the job. A small amount of liquid laundry detergent (such as Wisk) and chlorine bleach mixed into a gallon of warm water will clean most teak products. Apply this mixture with a stiff brush, and scrub lightly with the grain. Leave it on the wood for several minutes to give the detergent time to suspend the dirt and the bleach time to lighten the wood, then rinse thoroughly, scrubbing lightly with the grain. Use care on the rubber strips on the underside of the tray; simply wipe down with cleaner-do not scrub. The rubber strips will degrade over time. To order replacement strips, please contact MTI's service department at 800-783-8827.

There is a variety of teak cleaning products on the market, often sold where boating supplies are sold. Please follow manufacturers' directions for use.

NOTE: If a teak tray is used in conjunction with MTI's Teutonic shower enclosure, a small notch may need to be made in the teak tray to accommodate the bottom glass clip of the enclosure.

RADIANCE[®] OPERATION

- To turn the system on, press the on/off button - the keypad light will be on.
- Radiance is designed to be left on continually as the initial heating can take up to an hour. The system uses less energy than a standard light bulb.
- To turn the system off, press the on/off button once.



Radiance Keypad